

TOP-LIGHT-P² / -P³

Incident light

- >> modular and extremely versatile
- >> compact housing
- >> well-priced design
- >> easy and versatile mounting
- >> for continuous, switched and pulsed operation
(depending on type)



TOP-LIGHT-P²



TOP-LIGHT-P³

Technical specifications



Housing	Aluminium, black or natural anodised
Front cover (within the scope of supply)*	Acrylic clear, antireflective coating 2mm
Total weight	P ² : approx. 160g; P ³ : approx. 215g
Operating / ambient temperatur	max. 50°C recommended
IP protection class	depending on the version
Connector	M8 plug (4-pin)**
Supply voltage***	24VDC type or 12VDC type: 24VDC resp. 12VDC SC type: For use in conjunction with a controller
Number of LEDs	P ² : 96; P ³ : 144
LED lifetime	The LED lifetime of our lights is very high, but depends on many different factors such as ambient temperature, current load, and so on. Further information is available in the Technical information LED lifetime .

* more information and further front covers see section Accessories

** Cable not included in the scope of supply

*** more information see section Operating modes

Characteristics

Colour *	LED characteristics		typical characteristics per light					
	Wavelength (approx.)	Viewing angle	Current demand (24V type) ** / constant current max. (SC type) [mA]		Pulse current max. (SC type) *** [A]		Intensity **** [W/m ²]	
			P ²	P ³	P ²	P ³	P ²	P ³
red	617nm	30°	230	330	1,2	1,8		
red	635nm	120°	115	175	1,2	1,8		
white	6500K	120°	210	315	1,2	1,8		
IR	850nm	30°	135	200	4,8	7,2		

* other colours and types from UV to infrared on request

** stated current values of the 24V types should be considered approximate values

*** depending on the strobe conditions, recommended maximum values for a flash time of 1ms

**** approximately data measured in DC mode; Measuring distance 150mm



Safety note!

LED light systems can produce very intense radiation, which may possibly damage the eyes on improper use. Do not look directly into the light beam with unprotected eyes! Use eye protection!

Operating modes

24VDC type / 12VDC type

The lights are designed depending on the version for continuous operation at 24VDC or 12VDC.

The following operating modes are possible:

- DC operation at an appropriate power supply with 24VDC or 12VDC
- Switched operation with a matching power supply e.g. via PLC, opto-relay or controller (GS or SC series)
- Brightness-controlled operation via controller (GS or SC series) in conjunction with suitable power supply
- Pulsed mode via controller (GS or SC series) in conjunction with suitable power supply. The LED current can be increased in pulse mode up to a factor of 2 to 3.

SC type

For pulsed, switched or brightness-controlled operation, the lights are also available as optimized SC versions. They can be used in combination with our controllers of the GS and SC series and provide optimized and maximum current flow, especially in pulsed operation. We will assist you in selecting the right components.

Büchner Lichtsysteme GmbH

Uzstrasse 2
86465 Welden
Germany

Tel.: +49 (0)8293 | 909 112
Fax: +49 (0)8293 | 909 111

E-mail: info@buechner-lichtsysteme.de
Web: www.buechner-lichtsysteme.de

www.imaging-light-technology.com

TOP-LIGHT-P² / -P³

Incident light

Dimensions

TOP-LIGHT-P²

TOP-LIGHT-P³

PIN assignment connector

M8 plug 4-pin
(Front view on housing)

24VDC type		
PIN	Colour	Function
1	brown	+ 24V
3	blue	-

12VDC type		
PIN	Colour	Function
2	white	+ 12V
3	blue	-

SC type		
PIN	Colour	Function
4	black	+
3	blue	-

Application notes (Incident light)

Using on light

Using multiple lights

Light which hits the surface from a specific angle physically produces a slightly inhomogeneous light spot, depending on the inclination. By using a symmetrical arrangement of several lights this occurring intensity drop can be compensated and increases additionally the intensity in the field of view.

Accessories

Front covers / diffusers

Through the use of different diffuse front covers, the optical characteristics of the illumination can be changed. More information can be found in the **Technical information Front materials**.

technical changes reserved

Büchner Lichtsysteme GmbH

Uzstrasse 2
86465 Welden
Germany

Tel.: +49 (0)8293 | 909 112
Fax: +49 (0)8293 | 909 111

E-mail: info@buechner-lichtsysteme.de
Web: www.buechner-lichtsysteme.de

www.imaging-light-technology.com

